

Specifications for LV-WX300ST



Product Information

Type	
Product type	Projector
Imaging device, number	DMD x1
DMD	
Number of pixels	1280 x 800 (WXGA)
Size / Aspect ratio	0.65 type / 16:10
Projection lens	
Zoom ratio / Focal length / F value	Fixed / 6.9mm / F2.60
Projection distance	0.74 - 1.26m
Projection distance for 100"	1.05m
Projection ratio ^(*1)	0.49:1
Operation	Focus: manual
Light source	
Lamp type	Super-high pressure mercury lamp
Lamp power	210 / 170W (Lamp mode: normal / eco)
Images	
Optical system	Time division colour extraction, sequential display
Brightness	3000 / 2200lm (Lamp mode: normal / eco)
Marginal lamination ratio	70%
Contrast ratio	2300:1
Image size ^(*2)	70 – 120 type
Amount of lens shift	55%, fixed

Electrical zoom (by length)	2x maximum
Keystone correction range	V -18° / +12°
Image signal	
Analog PC input	UXGA / SXGA+ / WXGA+ / FWXGA / WXGA / SXGA / XGA / SVGA / VGA / MAC
Digital PC input	UXGA / SXGA+ / WXGA+ / FWXGA / WXGA / SXGA / XGA / SVGA / VGA
Digital video input	1080p / 1080i / 720p / 576p / 480p
Component video input	1080p / 1080i / 720p / 576p / 576i / 480p / 480i
Video input	NTSC / PAL / SECAM / NTSC4.43 / P AL-M / PAL-N / PAL-60
S video input	NTSC / PAL / SECAM / NTSC4.43 / P AL-M / PAL-N / PAL-60
Terminal	
Mini D-sub 15pin x 2	Analog RGB / Component video input
HDMI	Digital RGB / Digital video input
RCA	Composite video input
Mini DIN4	S-video input
Mini Jack	Stereo audio input
Mini Jack	Stereo audio output
Dsub9	RS-232C connection
RJ45	100BASE-TX / 10BASE-T
USB type B	Service port
Mechanics	
Adjustable feet	Front: 1, Rear: 1 (the angle of elevation of up to 6°)
Speaker	10W monaural
Dimensions (W x H x D)	W: 282mm, H: 117.9mm, D: 267.5mm (including protrusion) W: 282mm, H: 91mm, D: 267.5mm (not including protrusion)
Weight	2.8kg (6.2lbs)
Noise	36 / 29dB
Others	
Power supply	AC100V - 240V 50 / 60Hz
Power consumption	330W / 275W (Lamp mode: normal / eco)
Standby power consumption	3.0W (Standby) When setting is: Standby LAN:On 0.5W (Standby) When setting is: Standby LAN:Off

Operating temperature	0°C (32°F) to 40°C (104°F)
Accessories	Remote control, remote control dry-cell batteries, power cord, PC cable, User's Manual, Important Information and Warranty Card

*¹ Calculated value for 100" image

*² Images with the same aspect ratio as the digital micromirror device (DMD)



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: 022-28853054 to 60
- **Email**: itsolutions@varay.co.in