

## Specifications for imageRUNNER 2530



Device	imageRUNNER 2530	
Type	Desktop (Reader Combined + Inner Output)	
Imaging System	Laser Dry Electrostatic Transfer System	
Memory	Standard:	256MB
	Maximum:	512MB
Network Interface	Ethernet (100Base-TX / 10Base-T), USB 2.0	
Warm Up Time	30 seconds maximum after powering ON 1 second maximum from the Sleep mode	
First Copy Output Time	5.4 seconds or less	
Multiple Copies	1 to 999 sheets	
Magnification	25% to 400% (1% increment)	
Maximum Original Size	Max. A3 / 11" x 17"	
Duplex	Standard	
Copy / Print Speed	30ppm	
Resolution	Reading:	600 x 600dpi
	Writing:	1200 x 1200dpi
Paper Sources (80gsm)	Paper Cassette:	Standard: 250 + 550 sheets paper capacity Maximum: 250 + 3 x 550 sheets paper

		capacity
	Stack Bypass:	Standard: 100 sheets paper capacity
Acceptable Paper Weights	Paper Cassette:	64 to 90gsm
	Stack Bypass:	64 to 128gsm
Main Unit Dimensions (W x D x H)	565 x 680 x 806mm (with the platen cover) 565 x 693 x 896mm (with the feeder)	
Weight	Approx. 67.7kg	
Power Source	220 - 240V AC, 50 / 60Hz	
Maximum Power Consumption	Approx. 1.542KW	
Toner Yield (6% Coverage)	Approx. 14,600 sheets (A4)	
Drum Yield	Approx. 132,000 sheets (A4)	
<b>Print Specification</b>		
PDL	Standard:	UFR II LT
	Optional:	PCL 5e/6, PS3
Network OS	Windows 2000 / XP / Server2003 / Vista / Server2008 / Win7, Mac OSX (10.4.9 or later)	
<b>Network ScanGear Specification</b>		
Supported OS	Windows 2000 / XP / Server2003 / Vista / Server2008 / Win7	
Resolution	BW:	Up to 600 x 600dpi
	CL:	Up to 300 x 300dpi



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: +022-28460505 (50 lines)
- **Email**: [itsolutions@varay.co.in](mailto:itsolutions@varay.co.in)

