

## Specifications for imageRUNNER ADVANCE 6275



Type	Monochrome Laser Multifunctional (Reader / Printer Separated)	
Maximum Original Size	A3	
Copy Sizes	Left / Right Cassette 1, 2:	A4, B5
	Cassette 3, 4:	A3, B4, A4, A4R, B5, B5R, A5R
		Custom Size 139.7 x 182mm to 297 x 487.7mm
	Multi Purpose Tray:	A3, B4, A4, A4R, B5, B5R, A5R
Custom Size / Free Size 100 x 148mm to 297 x 487.7mm		
Resolution	Reading:	600 x 600dpi
	Copying:	600 x 600dpi
	Printing:	1200 x 1200dpi (Text / Line only)
Copy / Print Speed	A4:	75ppm (B&W)
	A3:	37ppm (B&W)
Magnification	Copy Ratio:	25 - 400% in 1% increment
First Copy Time	3.1 seconds or less	
Warm-Up Time	30 seconds or less	

Multiple Copies / Prints	1 to 9,999 copies	
Paper Weight	Left / Right Cassette 1, 2:	52 to 220gsm
	Cassette 3, 4:	52 to 220gsm
	Stack Bypass:	52 to 256gsm
Paper Capacity (80gsm)	Upper Left / Right Cassette 1, 2:	1,500 sheets x 2
	Cassette 3, 4:	550 sheets x 2
	Multi Purpose Tray:	100 sheets
	Paper Deck (Optional):	3,500 sheets
CPU	1.8GHz	
Memory	2GB (Optional 512MB memory for colour scan and send above 300dpi)	
Hard Disk Drive	Standard 160GB (Available space 15GB) / Optional 1TB (Available space 629GB)	
Interface	Ethernet (1000BaseT / 100Base-TX / 10Base-T) USB 2.0 Hi-speed, 2 x USB Host	
Power Supply	220-240V ( $\pm 10\%$ ), 50 / 60Hz ( $\pm 2$ Hz), 10Amp	
Power Consumption	2.2kW or less	
Toner (Estimated Yield @ 6% Coverage)	BW:	56,000
Drum Yield	BW:	6,000,000
Dimensions (W x D x H) (With the Duplex Colour Image Reader Unit-G1)	Without the upright control panel:	1,220 x 645 x 770mm
	With the upright control panel:	1,252* <sup>1</sup> x 1,481* <sup>2</sup> x 770mm
Weight	Approximately 234kg (Including the toner bottle and the Duplex Colour Image Reader Unit-G1)	
	* <sup>1</sup> To the top of the upright control panel in the standard position * <sup>2</sup> To the right edge of the upright control panel in the rightmost position	

<b>Print Specification</b>		
PDL	UFR II (Standard), PCL5e/6 (Optional), Adobe PostScript 3 (Optional)	
Resolution	1200 x 1200dpi (Text / Line only)	
Memory	Standard:	1.5GB RAM
CPU	Canon Custom Processor, 1.2GHz (Uses Main unit CPU)	
PS Fonts	Roman 136	
PCL Fonts	Roman93, Bitmap10, OCR2	
Supported OS	PCL:	Windows 2000 / XP / Server2003 / Vista / Server2008 / Win7
	Adobe PostScript 3:	Windows 2000 / XP / Server2003 / Vista / Server2008 / Win7, Mac OSX
UFR II	Windows 2000 / XP / Server2003 / Vista / Server2008 / Win7, Mac OSX (10.4.9 or later)	
Mac-PPD	Mac OS 9.1 or later, Mac OSX (10.2.8 or later)	
Interface	Ethernet (1000BaseT / 100Base-TX / 10Base-T), USB 2.0	
Network Protocol	TCP / IP (LPD / Port9100 / WSD / IPP / IPPS / SMB / FTP), IPv6, IPX / SPX (NDS, Bindery), AppleTalk	
Pull Scan	Network TWAIN Driver (75 to 600dpi 24bit Colour / 8bit Grayscale / 2bit Black & White)	
<b>Send Specification (Standard)</b>		
Scan Speed (A4, 300dpi)	Black & White:	120ipm
	Colour:	85ipm
Scan Resolution	600 x 600dpi*	
Destinations	Email / Internet FAX (SMTP), PC (SMB, FTP), WebDAV	
Address Book	LDAP, Local (Max. 1800)	
File Format	TIFF, JPEG, PDF, XPS, High compression PDF / XPS, Searchable PDF / XPS, PDF / A-1b, Office Open XML (Power Point)	
	* Requires optional 512MB memory	



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: +022-28460505 (50 lines)
- **Email**: [itsolutions@varay.co.in](mailto:itsolutions@varay.co.in)