

Specifications for imageCLASS LBP7110Cw



Print	
Printing Method	Colour Laser Beam Printing
Fixing Method	On Demand Fixing
Print Speed	Mono: 14ppm (A4 / Letter)
	Colour: 14ppm (A4 / Letter)
Print Resolution	600 x 600dpi
	9600 (equivalent) x 600dpi
	1200 x 1200dpi (equivalent)
First Printout Time (FPOT)	18/18secs. (A4 / Letter)
Warm-up Time (from Power On)	20secs. or less
Recovery Time (from Deep Sleep)	Approx. 4secs.
Print Language	UFR II LT
Paper Handling	
Paper Input (based on 80g/m ²)	150 sheets
Paper Output (based on 80g/m ²)	125 sheets (Face-Down)
Paper Size	A4 / B5 / A5 / Letter / Legal* / Executive / 16K / Foolscap / Statement / Envelope COM-10 / Envelope Monarch /

	Envelope C5 / Envelope DL / 3 x 5 index card / Custom (Width: 83 ~ 215.9mm x Length: 127.0 ~ 355.6mm) * Legal refers to paper measuring 215.9 x 355.6mm (8.5 x14 inches)	
Paper Weight	60 ~ 220g/m ²	
Print Margins	5mm-top, bottom, left and right (Envelope: 10mm)	
Connectivity and Software		
Standard Interfaces	Wired:	USB 2.0 High Speed 10Base-T/100Base-TX
	Wireless:	IEEE802.11b/g/n (Infrastructure Mode, WPS Easy Setup)
Compatible Operating Systems	Windows:	Windows XP (32bit / 64bit) / Windows Server 2003 (32bit / 64bit) / Windows Vista (32bit / 64bit) / Windows Server 2008 (32bit / 64bit) / Windows Server 2008 R2 (64bit) / Windows 7 (32bit / 64bit)
	Macintosh:	Mac OS 10.6 and above* ¹
	Linux	
	Citrix	
General Specifications		
Operation Panel	4 Keys, 12 LEDs	
Device Memory	64MB	
Noise Level* ³	During Operation:	6.52B or less (Sound Power) Approx. 49dB (Sound Pressure)
	During Standby:	Inaudible (Sound Power)* ⁴ Inaudible (Sound Pressure)* ⁴
Power Consumption	Maximum:	800W or less
	During Operation:	Approx. 340W
	During Standby:	Approx. 10W
	During Sleep:	Approx. 0.9W/4W (wireless)
Energy Star TEC (Typical Electricity Consumption)	0.4 kWh/week	
Dimensions (Width x Depth x Height)	406 x 454 x 255mm (Excluding protrusion)	

Weight (without Cartridge)	Approx. 16.6kg	
Power Requirements	220-240V (±10%), 50/60Hz (±2Hz)	
Operating Environment	Temperature:	10~30°C
	Humidity:	20~80%RH (No Condensation)
Toner Cartridge* ⁵	Cartridge 331 Black:	1,400 pages (Bundled Cartridge: 800 pages)
	Cartridge 331 II Black:	2,400 pages
	Cartridge 331 CMY:	1,500 pages (Bundled Cartridge: 800 pages)
Monthly Duty Cycle* ⁶	30,000 pages	
Recommended Monthly Print Volume	200 - 1,000 pages	

Specifications are subject to change without notice. :

*¹ The latest drivers for Mac OS can be downloaded from www.canon-asia.com when available.

*² The latest drivers for Linux can be downloaded from www.canon-asia.com when available.

*³ Tested in accordance to ISO7779 and declared per ISO9296.

*⁴ "Inaudible" means each sound pressure level at bystander's position is less than the absolute criterion value (about background noise) of ISO 7779.

*⁵ Toner cartridge yield in accordance with ISO / IEC 19798.

*⁶ Monthly Duty Cycle value provides a means for comparison of product robustness in relation to other Canon Laser Devices, and does not refer to actual maximum image output per month.



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: +022-28460505 (50 lines)
- **Email**: itsolutions@varay.co.in