

Specifications for imageCLASS LBP7780Cx



Print		
Printing Method	Colour Laser Beam Printing	
Fixing Method	On Demand Fixing	
Print Speed	Simplex:	Mono: 32/33ppm (A4 / Letter) Colour: 32/33ppm (A4 / Letter)
	Duplex:	27.6/28.9ppm 13.8/14.5spm (sheets/min)
Print Resolution	600 × 600dpi	
	9600 (equivalent) × 600 dpi	
First Printout Time (FPOT)	Mono:	10.2secs. (A4/Letter)
	Colour:	10.4secs. (A4/Letter)
Warm-up Time (from Power On)	39secs. or less	
Recovery Time	From Engine Sleep:	Approx. 7secs.
	From Deep Sleep:	Approx.30secs.
Print Language	UFR II, PCL5c/6, Postscript 3, PDF, XPS	
Paper Handling		
Paper Input (based on 80g/m ²)	Standard Cassette:	500 sheets
	Multi-Purpose Tray:	100 sheets

	Optional Paper Feeder (PF-723A):	500 sheets
	Maximum Paper Capacity:	1,100 sheets
Paper Output (based on 80g/m ²)	200 sheets (Face-Down)	
Paper Size	Standard Cassette:	A4 / B5 / A5 / A6 / Letter / Executive / 16K / Statement / Custom (Width: 101.6~215.9(* ¹)mm x Length: 148~297.0(* ²)mm) (* ¹): when width is 215.9mm, max length is 279.4mm (* ²): when length is 297.0mm, max width is 210.0mm
	Multi-Purpose Tray:	A4 / B5 / A5 / A6 / Letter / Legal* / Executive / Foolscap / 16K / Statement / Envelope COM-10 / Envelope C5 / Envelope Monarch / Envelope DL / 3 x 5 index card / Custom (Width: 76.2 ~ 215.9mm x Length: 127.0 ~ 355.6mm) * Legal refers to paper measuring 215.9 x 355.6mm (8.5 x 14 inches)
	Optional Paper Feeder (PF-723A):	A4 / B5 / A5 / Letter / Legal* / Executive / Foolscap / 16K / Custom (Width: 148 ~ 215.9mm x Length: 210.0 ~ 355.6mm) * Legal refers to paper measuring 215.9 x 355.6mm (8.5 x 14 inches)
Paper Weight	Standard Cassette:	60~163g/m ²
	Multi-Purpose Tray:	60~216g/m ²
	Optional Paper Feeder (PF-723A):	60~176g/m ²
Paper Type	Plain Paper / Heavy Paper / Transparency / Recycled Paper / Label / Envelope	
Print Margins	5mm-top, bottom, left and right (Envelope: 10mm)	
Duplex Printing	A4 / B5 / A5 / Letter / Legal* / Executive / Foolscap / 16K / Custom (Width: 148.0 ~ 215.9mm x Length: 210.0~355.6mm) Recommended Paper Weight: 60 - 163g/m ² * Legal refers to paper measuring 215.9 x 355.6mm (8.5 x 14 inches)	

Connectivity and Software		
Standard Interfaces	USB:	USB 2.0 High Speed USB 2.0 (Host x 2)
	Network:	10Base-T/100Base - TX/1000Base-T
	Expansion Interface:	SD Card Slot
Compatible Operating Systems	Windows:	Windows XP (32bit / 64bit) / Windows Server 2003 (32bit / 64bit) / Windows Vista (32bit / 64bit) / Windows Server 2008 (32bit / 64bit) / Windows 7 (32bit / 64bit)
	Macintosh:	Mac OS 10.5.8 and above* ¹
	Linux	
	Citrix	
General Specifications		
Device Memory	768MB	
Optional ROM	Barcode Printing Kit-F1	
Standard Fonts	93 Scalable, 10 Bitmap fonts, 136 PostScript fonts	
SD Card	Canon SD Card-B1 (8GB)	
Operation Panel	5 Line LCD 12 Keys, 8 LEDs	
Noise Level* ³	During Operation:	7.0B or less (Sound Power) Approx. 52dB (Sound Pressure)
	During Standby:	5.3B or less (Sound Power) Approx. 32.4dB (Sound Pressure)
Power Consumption	Maximum:	1,270W or less
	During Operation:	Approx. 580W
	During Standby:	Approx. 35W
	During Sleep:	Approx. 1W
Energy Star TEC (Typical Electricity Consumption)	1.6kWh/week	
Dimensions (Width x Depth x Height)	517 x 530 x 401mm	
Weight (without Cartridge)	Approx. 31.5kg (Without Cartridge)	
Power Requirements	220 - 240V, 50/60Hz (±2Hz)	

Operating Environment	Temperature:	10 ~ 30°C
	Humidity:	20 ~ 80%RH (No Condensation)
Toner Cartridge* ⁴	Cartridge 332 Black:	6,100 pages
	Cartridge 332 II Black:	12,000 pages
	Cartridge 332 CMY:	6,400 pages
Waste Toner Box	WT-723:	18,000 pages
Monthly Duty Cycle* ⁵	75,000 pages	
Recommended Monthly Print Volume	1,250 - 5,000 pages	

Specifications are subject to change without notice. :

*¹ The latest drivers for Mac OS can be downloaded from www.canon-asia.com when available.

*² The latest drivers for Linux can be downloaded from www.canon-asia.com when available.

*³ Tested in accordance to ISO7779 and declared per ISO9296.

*⁴ Toner cartridge yield in accordance with ISO/IEC 19798.

*⁵ Monthly Duty Cycle value provides a means for comparison of product robustness in relation to other Canon Laser Devices, and does not refer to actual maximum image output per month.



- **Address :** Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No:** +022-28460505 (50 lines)
- **Email:** itsolutions@varay.co.in