

Specifications for imageCLASS MF4720w



PRINT	
Printing Method	Monochrome Laser
Print Speed (Simplex; A4/LTR)	Up to 23 / 24ppm (pages per minute)
Print Resolution	600 x 600dpi
Print Quality with Image Refinement Technology	1200 (equivalent) x 600dpi
Warm up Time (From Power On)	13.5 secs or less
Recovery Time (From Sleep Mode)	Approx. 2.0 secs.
First Printout Time (FPOT)	Approx. 6 / 5.8 secs (A4/LTR)
Print Language	UFR II LT
Print Margins	5 mm-top, bottom, left and right (Other sizes than Envelope) 10 mm-top, bottom, left and right (Envelope)
Print Features	Watermark, Page Composer, Toner Saver
COPY	
Copy Speed (Simplex; A4/LTR)	Up to 23 / 24ppm (copies per minute)
Copy Resolution	600 x 600dpi
First Copy Time (FCOT)	Approx. 9.0 / 8.7 secs (A4/LTR)
Maximum Number of Copies	Up to 99 copies

Reduce / Enlargement	25 - 400 % in 1% increments
Copy Features	Memory Sort, 2 on 1, 4 on 1, ID Card Copy
SCAN	
Scan Resolution	Optical: Up to 600 x 600dpi Driver Enhanced: Up to 9600 x 9600dpi
Color Depth	24-bit
Pull Scan	Yes, USB and Network
Push Scan (Scan To PC) with MF ToolBox	Yes, USB and Network
Scan Features	TWAIN, WIA (Scan Driver Compatibility)
PAPER HANDLING	
Paper Input (Standard)	Plain Paper (60-80g/m ²): 250-sheet Cassette, 1-sheet Multipurpose Tray
Paper Output	100 sheets (face down , 20lb LTR / 68g/m ² A4)
Paper Sizes (Standard Cassette)	A4, B5, A5, LGL*, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard Envelope: COM10, Monarch, C5, DL, Custom (Min. 76.2 x 210mm to Max. 216 x 356 mm) * LGL refers to paper measuring 215.9 x 355.6mm (8.5 x14 inches)
Paper Sizes (Multipurpose Tray)	A4, B5, A5, LGL*, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard Envelope: COM10, Monarch, C5, DL, Custom (Min. 76.2 x 127mm to Max. 216 x 356 mm) * LGL refers to paper measuring 215.9 x 355.6mm (8.5 x14 inches)
Paper Types	Plain, Heavy, Recycled, Transparency, Label, Envelope
Paper Weight (Standard Cassette)	60 to 163 g/m ²
Paper Weight (Multipurpose Tray)	60 to 163 g/m ²
CONNECTIVITY & SOFTWARE	
Standard Interface(s) (Wired)	USB 2.0 Hi-Speed, 10 / 100 Base-T/Base-TX Ethernet (Network)
Standard Interface(s) (Wireless)	Wi-Fi 802.11b/g/n (Infrastructure mode, WPS easy setup)
Network Protocol	Print: LPD, RAW, WSD-Print (IPv4, IPv6) Scan: WSD-Scan (IPv4, IPv6) TCP/IP Application Services: Bonjour (mDNS), DHCP,

	BOOTP, RARP, Auto IP (IPv4), DHCPv6 (IPv6) Management: SNMPv1 (IPv4, IPv6)	
PRINT		
Network Security (Wired)	IP / Mac address filtering	
Network Security (Wireless)	WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES), 802.1x (LEAP, EAP-FAST, PEAP, EAP-TLS, EAP-TTLS)	
One-Push Wireless Configuration	Wi-Fi Protected Setup (WPS)	
Compatible Operating Systems * ²	Windows 8 (32 / 64-bit), Windows 7 (32 / 64-bit), Windows Vista (32 / 64-bit), Windows XP (32 / 64-bit), Windows 2000, Windows Server 2003 (32 / 64-bit) * ¹ , Windows Server 2008 (32 / 64-bit)* ¹ Mac OS X 10.4 - 10.8, Linux * ³	
Software Included	Printer driver, Scanner driver, MF Toolbox, Presto! PageManager, SSID Tool	
GENERAL SPECIFICATIONS		
Memory	128MB	
LCD Display	5-line BW LCD (Vari-Angle Operation Panel)	
Dimensions	390 x 362 x 301mm (Cassette closed) 390 x 439 x 301mm (Cassette opened)	
Weight	Without cartridge	10.0kg
	With cartridge	10.5kg
Power Consumption	Maximum:	1320W or less
	During Operation:	Approx. 560W (Average; Copying)
	During Standby:	Approx. 3.5W
	During Sleep:	Approx. 1.4W / 2.4W(wireless)
Noise Levels * ⁴	During Operation:	Sound Pressure Level (Bystander's position): 50dB in Printing (reference value) Sound Power Level: 6.5B in Printing
	During Standby:	Sound Pressure Level (Bystander's position): Inaudible (reference value) * ⁵ Sound Power Level: 4.3B or less
Operating Environment	Temperature: 10 to 30°C	
	Humidity: 20% to 80% RH (no condensation)	

Power Requirements	AC 220 to 240V: 50 / 60Hz
Toner Cartridge * ⁶	Cartridge 328: 2,100 pages (Bundled cartridge: 1,000 pages)
Monthly Duty Cycle * ⁷	Up to 8,000 pages

Specifications are subject to change without notice. :

*¹ ScanGear and MF Toolbox are not available for Windows Server 2003/2008.

*² Check [here](#) for printer driver updates

*³ Only print function is supported in Linux

*⁴ Tested in accordance to ISO7779 and declared per ISO9296.

*⁵ "Inaudible" means each sound pressure level at bystander's position is less than the absolute criterion value (about background noise) of ISO 7779.

*⁶ Toner cartridge yield in accordance with ISO/IEC 19752

*⁷ Monthly Duty Cycle value provides a means for comparison of product robustness in relation to other Canon Laser Devices, and does not refer to actual maximum image output per month.



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: +022-28460505 (50 lines)
- **Email**: itsolutions@varay.co.in