

Specifications for canon digital slr camera eos-6d (wg) 24-70 is



Technical Details

Auto Focus Technology	<ul style="list-style-type: none">• Contrast Detect (sensor)• Phase Detect• Multi-area• Selective single-point• Single• Continuous• Face Detection• Live View
Autofocus Points	11
Color	Black
Compatible Mountings	Canon EF
Configuration	Base
Continuous Shooting Speed	4.5 fps
Display	LCD
Display Fixture Type	Fixed
Display Resolution Maximum	1040000

Display Size	3 inches
Effective Still Resolution	20.2 MP
Expanded ISO Maximum	102,400
Expanded ISO Minimum	50
External Memory Included	No
File Format	JPEG (Exif 2.3), RAW: RAW (5472 x 3648), M RAW (4104 x 2736), S RAW (2736 x 1824) (14bit, Canon original RAW 2nd edition)
Flash Memory Type	SD/SDHC/SDXC
Flash Modes Description	Auto, Second curtain synchro
Flash Sync Speed	1/180 sec
Flash Type	Hot shoe
Focus Description	TTL-CT-SIR
Focus Type	Includes Manual Focus
Form Factor	Mid-size SLR
GPS	BuiltIn
HDMI Type	HDMI Mini
ISO Range	Auto, 100 - 25600 in 1/3 stops, plus 50, 51200, 102400 as option
Image Aspect Ratio	3:2
Image Stabilization	None
Included Components	<ul style="list-style-type: none"> • EOS 6D Body • EF 24-105mm f/4L IS USM Lens • Eyecup Eb (Not Shown) • Camera Cover R-F-3 • Battery Pack LP-E6 • Battery Charger LC-E6 • Stereo AV Cable AVC-DC400ST • Wide Neck Strap EW-EOS 6D • USB Interface Cable IFC-200U • Lens Cap E-77U (Not Shown) • Lens Dust Cap E (Not Shown) • Lens Hood EW-83H
Item Dimensions	4.37 x 2.8 x 5.71 inches
Item Display Weight	1.7 pounds
Item Weight	1.7 pounds
Lens Type	Zoom
Lithium Battery Energy Content	13 Watt Hours
Lithium Battery Weight	80 grams
Manufacturer	Limited 1 year

Warranty Description	
Material Type	Magnesium alloy, polycarbonate top plate
Maximum Aperture	<i>f</i> /4
Maximum Shutter Speed	1/4000 of a second
Maximum horizontal resolution	5,472
Metering	Multi, Center-weighted, Spot, Partial
Minimum Aperture	<i>f</i> /22
Minimum Shutter Speed	30 seconds
Model Year	2013
Optical Sensor Resolution	20.2 MP
Optical Sensor Technology	CMOS
Optical Zoom	50x
Photo Filter Thread Size	77 mm
Photo Sensor Technology	CMOS
Processor Description	Digic 5+
Remote Control Description	Remote control with N3 type contact, Wireless Controller LC-5, Remote Controller RC-6
Self-timer	Yes
Sensor Cleaning Method	EOS integrated cleaning system
Shipping Weight	5.6 pounds
Style Name	w/ 24-105mm USM
Supported Battery Types	Lithium-Ion LP-E6 rechargeable battery & charger
USB 2.0	1
Video Capture Format	mpeg-4;h.264
Video Capture Resolution	1080p_hd
Viewfinder Magnification	0.71x

Viewfinder Type	Optical (pentaprism)
Weather Resistance	Splash and dust resistant

Product Description :

The Canon 8035B009 EOS 6D Digital SLR Camera with EF 24-105mm f/4L IS USM Standard Zoom Lens provides compatibility and convenience through its design and features. With the DIGIC 5+ image processor and 14-bit A/D conversion, the sensor is capable of recording imagery with expanded sensitivity up to ISO 102400. The processing power affords noise reduction techniques and the ability to record continuous still images up to 4.5fps. Full HD video recording is possible up to 1080/30p in the All I-frame or IPB compression, as well as the standard H.264/MPEG-4 AVC codec. When you record HD video, full manual control over exposure and sound enables you to take complete control over the final appearance of your movies. Built-in Wi-Fi and GPS technologies provide extensive connectivity to the 6D. The included standard zoom lens provides a useful range of focal lengths from wide angle to standard portrait length. It features Image Stabilizer Technology for reduction of camera shake.



- **Address :** Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No:** +022-28460505 (50 lines)
- **Email:** itsolutions@varay.co.in