

Specifications for imagePROGRAF iPF6410SE



Technology	
Printer Type	6 Colour - 24"
Number of Nozzles	2,560 nozzles x 6 colours, 1 print head
Print Resolution	2400 x 1200dpi
Nozzle Pitch	1200dpi x 2 rows
Line Accuracy	±0.1% or less
Ink Droplet Size	4 Picoliter
Ink Capacity	130ml or 300ml per colour Bundled Starter Ink: 90ml
Ink Type	Pigment ink - 6 colours (BK / MBK / C / M / Y / R)
Ink Supply Method	Tubing system (with sub-ink tank)
OS Compatibility	Windows® (XP / Vista 32 / 64bit / Windows 7 32 / 64bit) Macintosh® (OSX)
Printer Language	GARO (Graphic Arts language with Raster Operations)
Standard Interfaces (Built-in)	USB 2.0 Hi-Speed Ethernet 10/100 Base-T/TX
Printing Speed	
Printing Speed	34sec. (Fast Economy Mode)

(A1 size, Plain Paper)	58sec. (Fast Mode) 105sec. (Standard Mode)	
Printing Speed (A1 size, Coated Paper)	60sec. (Fast Mode) 105sec. (Standard Mode)	
Printing Speed (A1 size, Glossy Photo Paper)	118sec. (Fast Mode) 221sec.(Standard Mode)	
Memory		
Standard Memory	256MB	
Media Handling		
Media Width	Roll Paper:	203.2mm to 610mm
	Cut Sheet:	203.2mm to 610mm (Top Loading, Manual Feed)
Media Thickness	Roll Paper:	0.07mm to 0.8mm
	Cut Sheet:	0.07mm to 0.8mm (Top Loading, Manual Feed)
Minimum Printable Length	Roll Paper:	203.2mm
	Cut Sheet:	279.4mm
Maximum Printable Length	Roll Paper:	18m (varies according to the OS and application)
	Cut Sheet:	1.6m
Maximum Media Roll Diameter	150mm	
Media Core Size	Internal diameter of roll core: 2" or 3"	
Paper Feed Method	Roll Paper:	One Roll, Top Loading, Front Output
	Cut Sheet:	Top Loading Manual Feed: One sheet, Front Output
Borderless Printing Width (Roll Paper only)	10" (254mm), B4 (257mm), 14" (356mm), 16" (407mm), A2 (420mm), A2+/17" (432mm), B2 (515mm), A1 (594mm), 24" (610mm)	
Dimensions and Weight		
Physical Dimensions (W x D x H)	1,017 (W) x 702 (D) x 344 (H) mm Weight: approx. 44kg (excluding consumables and a printer stand)	
	1,017 (W) x 870 (D) x 991 (H) mm Weight: approx. 54kg (Main unit with basket opened and a printer stand excluding consumables)	

	Basket closed: 1,017 (W) x 751 (D) x 991 (H) mm 1,180 (W) x 916 (D) x 645 (H) mm Weight: approx. 74kg (Main unit with pallet)	
Power and Operating Requirements		
Power Supply	AC 100 to 240V (50 to 60Hz)	
Power Consumption	Operation:	100W or less
	Standby:	5W or less
	Power off (Standby)	0.5W or less
Operating Environment	Temperature:	15 to 30°C
	Humidity:	10 to 80% (Condensation-free)
Noise Level (Approx.)	Operation:	49dB (A) or less
	Standby:	35dB (A) or less
	Accoustic Power:	6.4 Bels or less
Environment Certifications	International Energy Star Program (WW), RoHS directive	

*¹ For the information of purchasable media, contact your local sales representative.



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: +022-28460505 (50 lines)
- **Email**: itsolutions@varay.co.in