

## Specifications Benq-MS661



### Benq-MS661 Specifications

|   |                               |
|---|-------------------------------|
| Projection System   | DLP                           |
| Native Resolution   | XGA (1024 x 768)              |
| Brightness*   | 3200AL                        |
| Contrast Ratio  | 13000:1                       |
| Display Color   | 1.07 Billion Colors           |
| Lens  | F=2.56-2.68, f=22.04-24.14 mm |
| Throw Ratio   | 1.96~2.15(78"±3% @ 3.1m)      |
| Image Size (Diagonal)   | 60"~300"                      |
| Zoom Ratio  | 1.1:1                         |
| Lamp Type   | 190W                          |
| Lamp Mode (Normal / Economic / SmartEco / LampSave / LumenCare) | 4500/6000/6500/10000 hours    |
| Projection Offset   | 120% ±5%                      |

|                                    |  |
|------------------------------------|--|
| Resolution Support                 | VGA(640 x 480) to WUXGA_RB(1920X1200) *RB=Reduced blanking   |
| Horizontal Frequency               | 15-102KHz  |
| Vertical Scan Rate                 | 23-120Hz   |
| Interface                          | Computer in (D-sub 15pin) x 2 (Share with component)<br>Monitor out (D-sub 15pin) x 1<br>Composite Video in (RCA) x 1<br>S-Video in (Mini DIN 4pin) x 1<br>HDMI x 1<br>Audio in (Mini Jack) x 1<br>Audio out (Mini Jack) x 1<br>Speaker 2W x 1<br>USB (Type B) x1<br>RS232 (DB-9pin) x 1<br>IR Receiver x1 (Front) |
| Dimensions(W x H x D)              | 283 x 95 x 222 mm (with feet)<br>283 x 88.7 x 222 mm (without feet)  |
| HDTV Compatibility                 | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p   |
| Video Compatibility                | NTSC, PAL, SECAM   |
| 3D Support and Compatibility       | Frame Sequential: Up to 720p<br>Frame Packing: Up to 1080p<br>Side by Side: Up to 1080i/p<br>Top Bottom: Up to 1080p   |
| Weight                             | 1.9 kg   |
| Power Supply                       | AC100 to 240 V, 50 to 60 Hz  |
| Picture Modes                      | Dynamic/Presentation/sRGB/Cinema/(3D)/User 1/User 2  |
| Accessories (Standard)             | Remote Control w/ Battery<br>Power Cord (by region)<br>UM Download Instruction and Regulatory Statements<br><br>Quick Start Guide<br>Warranty Card (by region)<br>VGA(D-sub 15pin) Cable   |
| Aspect Ratio                       | Native 4:3 (5 aspect ratio selectable)   |
| Keystone Adjustment                | 1D, Vertical $\pm 40$ degrees  |
| Audible Noise Normal Economic Mode | 33/28 dBA (Normal/Economic mode)   |

|  |   |
|--|---|
| Accessories(Optional)  | Spare Lamp Kit<br>Ceilling Mount<br>3D Glasses<br>Carry bag   |
| PointWrite Camera Module   |    |
| Power consumption  | Normal 270W, Eco 220W, Standby <0.5W  |
| Software  |   |
| On-Screen Display Languages  | Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/<br>Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/<br>Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/<br>Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/<br>Thai/ Traditional Chinese (28 Languages). |



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: +022-28460505 (50 lines)
- **Email**: [itsolutions@varay.co.in](mailto:itsolutions@varay.co.in)