

Specifications Hitachi CP EX400



Optical

- **LCD Panel**

0.63" MLA w/micro lens array

- **Resolution**

XGA (1024x768)

- **Brightness**

4200lm

- **Contrast Ratio**

2000:1

- **Focus**

Manual focus

- **Lamp Wattage**

225W

- **Lamp Life**

5000hr (Normal Mode) / 6000hr Target 10000hr (Eco Mode)

- **Focus distance**

0.9 ~ 9.1 m (WIDE), 1.0~10.9 m (TELE)

<ul style="list-style-type: none"> • Distance to width ratio
1.5 (Wide), 1.8 (Tele)
<ul style="list-style-type: none"> • Display Size
30"~300"
<ul style="list-style-type: none"> • Keystone correction
Manual V
<ul style="list-style-type: none"> • Number of colours
8 Bit/colour, 16.7M colours
<h2 style="color: red;">Features</h2>
<ul style="list-style-type: none"> • Computer compatibility
IBM Compatible VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, UXGA (compressed), MAC 16"
<h2 style="color: red;">Compatibility</h2>
<ul style="list-style-type: none"> • Composite/S-Video
NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, PAL (60Hz), SECAM
<ul style="list-style-type: none"> • Component Video/HDMI Video
480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz, 1080i@50/60Hz, 1080p@50/60Hz
<ul style="list-style-type: none"> • Plug & Play
DDC2B (excluding COMPUTER IN 2)
<ul style="list-style-type: none"> • Speakers
1W

<ul style="list-style-type: none"> • Picture Adjustments
Aspect selection (video, data, HDMI), Equalizing Digital Gamma Correction, Equalizing Colour temperature adjustment, 2-3 pull down for NTSC, Mirror reverse image, up-side down image, Progressive Scan, Noise Reduction, Overscan
<ul style="list-style-type: none"> • Advanced Features
MyScreen, My Memory, My Button (by remote control), My Text, My Source, Picture modes (normal, cinema, dynamic, blackboard, whiteboard, greenboard, daytime, photo), Source naming (English), Resolution setting, Filter timer, Stand-by Audio, Template, Closed Caption (for NTSC & component 480i only), Framelock, Eco Mode (normal, eco, intelligent eco, saver), ImageCare™
<ul style="list-style-type: none"> • Outward
Easy lamp replace from top, Easy access air filter
<ul style="list-style-type: none"> • Power on & off
Direct on, Auto off
<ul style="list-style-type: none"> • Security Systems
Password/My screen Password, pin lock, key lock, security bar and slot (for Kensington lock)
<ul style="list-style-type: none"> • OSD Languages
W/W Model 33-language OSD
Connections
<ul style="list-style-type: none"> • Digital input
HDMI x 1
<ul style="list-style-type: none"> • Computer Input
15-pin Mini D-sub x 2
<ul style="list-style-type: none"> • Monitor output
15-pin Mini-D-sub x 1 impossible to use COMPUTER IN 2 at the same time.
<ul style="list-style-type: none"> • Video Input

1 x RCA Jack (for composite)
<ul style="list-style-type: none"> • Audio Input
RCA jack L/R x1
<ul style="list-style-type: none"> • Audio output
RCA jack L/R x1
<ul style="list-style-type: none"> • Control
D-sub 9-pin jack x 1 (RS232C)
<p>Power</p>
<ul style="list-style-type: none"> • Power Supply
AC 100V-120V / 3.3A AC220-240V / 1.6A
<ul style="list-style-type: none"> • Power Consumption/Standby
320W/0.5W
<p>Physical</p>
<ul style="list-style-type: none"> • Dimensions (W X H X D)
320mmx85mmx245mm, 12.6"x3.3"x9.6" (Excluding feet and extrusions)
<ul style="list-style-type: none"> • Weight
Approx. 2.9kg

<ul style="list-style-type: none"> • Noise Level
29dB (Eco Mode)/37dB (Normal Mode)
<ul style="list-style-type: none"> • Operating Temperature
5-35°C
<ul style="list-style-type: none"> • Air Filter
Urethane, Replacement cycle: 2000hr (varies according to usage environment)
<h2 style="color: red;">Certification</h2>
<ul style="list-style-type: none"> • Certification
UL60950-1/cUL, FCC Part 15 subpart B class B, CE Marking: EN61000-3-2, EN61000-3-3, EN55022 (class B), EN55024 (EMC directive), EN60950-1 (Low voltage directive), WEEE, RoHS, ErP (lot6) compliant, c-tick class B (standard for Australia/New Zealand), GS mark.
<h2 style="color: red;">Accessories Supplied</h2>
<ul style="list-style-type: none"> • Accessories Supplied
Power cord, Computer Cable, Remote Control Unit with batteries, User's Manual CD (Operating Guide, Safety Instructions), User's Manual (Concise)
<h2 style="color: red;">Optional Accessories</h2>
<ul style="list-style-type: none"> • Remote Controller

HL03031
<ul style="list-style-type: none"> • Replacement lamp
DT01491
<ul style="list-style-type: none"> • Air Filter
UX38851(Up to 5000 hours)
<ul style="list-style-type: none"> • Long Ceiling Mount
HAS-304H
<ul style="list-style-type: none"> • Short Ceiling Mount
HAS-204L
<ul style="list-style-type: none"> • Ceiling Mount Bracket
HAS-EX300
<p>Warranty</p>
<ul style="list-style-type: none"> • Projector warranty
3 Years/6 Months** (For education and extended warranties please contact your local dealer)
<ul style="list-style-type: none"> • disclaimer
<p>*The stated lamp and filter life refers to the average life expected in ideal operating conditions with usage in accordance with the manual. The majority of, but not all lamps and filters should achieve this figure. **Where a lamp fails within warranty and a replacement lamp is taken, the warranty for the replacement lamp will be a maximum of 6 months (dependent on warranty hours stated). The specification above and photography is for reference only and may be subject to change.</p>



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: +022-28460505 (50 lines)
- **Email**: itsolutions@varay.co.in