

Specifications Hitachi CP X3030WN



Optical
<ul style="list-style-type: none">• LCD Panel
0.63" (1.6cm) P-Si TFT x 3
<ul style="list-style-type: none">• Resolution
XGA (1024x768)
<ul style="list-style-type: none">• White light output (brightness)
3200 ANSI Lumens (Normal Mode) 2100 ANSI Lumens (Eco Mode)
<ul style="list-style-type: none">• Brightness
3200 ANSI Lumens (Normal Mode) 2100 ANSI Lumens (Eco Mode)
<ul style="list-style-type: none">• Contrast Ratio
4000:1 (Presentation Mode)
<ul style="list-style-type: none">• Lens
Manual Focus, Manual Zoom x 1.2

<ul style="list-style-type: none"> • Lamp Wattage
215W UHP
<ul style="list-style-type: none"> • Lamp Life
5000 hours (Normal Mode) 6000 hours (Eco Mode)*
<ul style="list-style-type: none"> • Diagonal display size
30~300" (76~762cm)
<ul style="list-style-type: none"> • Number of colours
8 Bit/colour, 16.7M colours
<ul style="list-style-type: none"> • Keystone correction
6:1 upward shift, fixed
<ul style="list-style-type: none"> • Focus distance
0.8m~9.0m (Wide), 1.0~10.8m (Tele)
<ul style="list-style-type: none"> • Distance to width ratio
1.5 (Wide), 1.8 (Tele)
<h2 style="color: red;">Compatibility</h2>
<ul style="list-style-type: none"> • Computer compatibility
IBM Compatible VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, UXGA (compressed), MAC 16"
<ul style="list-style-type: none"> • Composite/S-Video
NTSC, PAL, SECAM, PAL-M, PAL-N, NTSC4.43
<ul style="list-style-type: none"> • Component Video
525i(480i), 525p(480p), 625i(576i), 1125i(1080i@50/60), 750p(720p@50/60), 1125p(1080p@50/60)
<ul style="list-style-type: none"> • HDMI Video
Signal: 525i(480i), 525p(480p), 625i(576i), 1125i(1080i@50/60), 750p(720p@50/60), 1125p(1080p@50/60)

<ul style="list-style-type: none"> • Plug & Play
DDC2B
<h2 style="color: red;">Features</h2>
<ul style="list-style-type: none"> • Speakers
16W x 1 (Mono)
<ul style="list-style-type: none"> • Basic functions
Freeze, Magnifying, Blank, Auto adjustment, Search, Page Up & Down (for USB mouse function), Auto signal search, Auto eco mode
<ul style="list-style-type: none"> • Picture Adjustments
Aspect selection (video, data, HDMI), Equalizing Digital Gamma Correction, Equalizing Colour temperature adjustment, 2-3 pull down for NTSC, Mirror reverse image, up-side down image, Progressive Scan, Noise Reduction, Overscan
<ul style="list-style-type: none"> • Digital Keystone Correction
Vertical $\pm 30^\circ$ (XGA @ 60Hz)
<ul style="list-style-type: none"> • Advanced features (CP-X3030WN)
MyScreen, My Memory, My Button, My Text, My Source, Picture mode (normal, cinema, dynamic, blackboard, whiteboard greenboard, photo), Daytime Mode, Input source naming (English), Resolution setting, Template, Closed Caption (for NTSC & component 480i only), Audio pass through, Frame lock, Audio ports assign, Cloning, Drawing function (Optional wireless pen tablet TB-1 is necessary), Eco Mode (normal, eco, intelligent eco, saver), iOS Connectivity, ImageCare™
<ul style="list-style-type: none"> • Outward
Easy lamp replace from top, Easy access air filter
<ul style="list-style-type: none"> • Power on & off
Direct on, Auto off
<ul style="list-style-type: none"> • Security Systems
Security bar, PIN-Lock, MyScreen Password, Key Lock (key pad and remote control), Kensington slot, Transition detector, My Text Password, Security label

<ul style="list-style-type: none"> • Network
<p>Network presentation (PC still/moving picture transfer), Configure and control projector via web browser, Receive alerts via e-mail, Projector management via SNMP, Crestron RoomView®, Scheduling, My Image, Displaying text data transferred via the network, Command Control via network, AMX Device Discovery, PJ Link™, Network Bridge</p>
<ul style="list-style-type: none"> • OSD Languages
<p>English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Arabic, Persian, Czech, Danish, Hungarian, Romanian, Slovenian, Croatian, Greek, Lithuanian, Estonian, Latvian, Thai, Portuguese (Brazil), Indonesian, Vietnamese</p>
<h2 style="color: red;">Connections</h2>
<ul style="list-style-type: none"> • Digital input
<p>1 x HDMI (HDCP compatible)</p>
<ul style="list-style-type: none"> • Computer Input
<p>2 x 15-pin Mini D-sub (shared with analogue component video input)</p>
<ul style="list-style-type: none"> • Monitor output
<p>15-pin Mini-D-sub x 1</p>
<ul style="list-style-type: none"> • Video Input
<p>2 x 15-pin Mini D-sub (shared with analogue computer in 1/2) 1 x RCA for composite 1 x Mini-DIN for S-Video</p>
<ul style="list-style-type: none"> • Audio Input
<p>2 x Stereo Mini Jack, 1 x pair RCA (L/R), 1 x Microphone Jack</p>
<ul style="list-style-type: none"> • Audio output
<p>1 x pair RCA (L/R)</p>
<ul style="list-style-type: none"> • USB T ype A
<p>1 x USB Type A (for USB display or USB mouse control)</p>

<ul style="list-style-type: none"> • USB Type B
2 x USB Type B (for PC-less presentation or wireless network)
<ul style="list-style-type: none"> • Wired network
1 x RJ-45
<ul style="list-style-type: none"> • Wireless network
IEEE802.11b/g/n ready (optional USB wireless adapter required)
<ul style="list-style-type: none"> • Control
1 x 9-pin for RS-232C control
<ul style="list-style-type: none"> • Power Supply
100-120V/220-240V, auto switching
<ul style="list-style-type: none"> • Power Consumption/Standby
310W/<0.5W (AC 220-240V)
<p>Physical</p>
<ul style="list-style-type: none"> • Dimensions (W X H X D)
320 x 85 x 245mm (excluding feet and extrusions)
<ul style="list-style-type: none"> • Weight
3.0Kg
<ul style="list-style-type: none"> • Noise Level
30dB (Eco Mode)/38dB (Normal Mode)
<ul style="list-style-type: none"> • Air Filter
Hybrid (up to 5000 hours)

Miscellaneous

- **Misc X2530**

Indicator lights (lamp, temp, power), Ceiling mount image, Rear projection image, Serial number label on side, MAC address label on side, MAC PC support

Certification

- **Certification CP-EX250**

UL60950-1/cUL, FCC Part 15 subpart B class B, CE Marking: EN61000-3-2, EN61000-3-3, EN55022, EN55024 (EMC Directive), EN60950-1 (Low voltage directive), WEEE, RoHS, ErP (lot6) compliant, c-tick class B

Accessories Supplied

- **Accessories Supplied CP-X2530WN**

Remote control with batteries (HL02881), Computer cable, Power cord, Lens cover, Adapter cover, Security label, User manual (detail & concise), Application CD

Optional Accessories

- **Replacement lamp**

DT01431

- **USB wireless adapter**

USB-WL-11N

- **Wireless pen tablet**

TB-1

- **Interactive camera unit**

Warranty

- **Projector warranty**

3 Years/6 Months**

- **Lamp warranty (education)**

For education and extended warranties please contact your local dealer

- **Disclaimer (CPWX12WN)**

*The stated lamp and filter life refers to the average life expected in ideal operating conditions with usage in accordance with the manual. The majority of, but not all lamps and filters should achieve this figure. **Where a lamp fails within warranty and a replacement lamp is taken, the warranty for the replacement lamp will be a maximum of 6 months (dependent on warranty hours stated). HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. The specification above and photography is for reference only and may be subject to change.



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: +022-28460505 (50 lines)
- **Email**: itsolutions@varay.co.in