

Specifications Infocus IN 3126



Infocus IN 3126 Specifications

Native Aspect Ratio	16x10
Technology	DLP
Resolution	WXGA(1280x800)
Lumens (Eco/High)	3400/4000
Contrast	3000
3D	Yes Supports PC-based 3D content
Closed Captioning	Yes
Speakers	10W x 2
Audible Noise (Eco/High, dBA)	31 dB/33 dB
Keystone	± 40°V
Lamp	SP-LAMP-078
Lamp Hours (Eco/High)	2000/3000

Connections	HDMI, VGA x 2, USB Type A (PC-less Display or optional wireless LAN), USB Mini-B (for display or presentation control), Component, Composite, S-Video, RCA stereo audio in x 2, 3.5mm microphone in, LAN (RJ45), USB Type B (for firmware)
Image Offset	29
Lens Shift: Horz (min/max)	None
Lens Shift: Vert (min/max)	None
Throw Ratio	2.12~1.44
Weight(lbs/kg)	8.1/3.7
Product Dimensions HxWxD	10.4in x 12.8in x 4.8in (265mm x 326mm x 122mm)
Shipping Weight(lbs/kg)	10.4/4.7
Shipping Dimensions HxWxD	13.5in x 15in x 9.6in (340mm x 385mm x 245mm)
Power consumption (Max, Watts)	
Product Warranty	2 Years
Lamp Warranty	6 Months
Accessory Warranty	90 Days
Approvals	UL & CUL (USA and Canada), FCC (USA), CE (Europe), C-Tick (Australia), NOM+Eco (Mexico), CCC+CECP (China), IRAM (Argentina), PSB (Singapore), SASO (Saudi Arabia), CB, Nemco/GS, VCCI, PCT, KC, PSE.



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: +022-28460505 (50 lines)
- **Email**: itsolutions@varay.co.in