

## Specifications for DR 6030C



<b>Type</b>	Desktop sheet-fed scanner	
<b>Document Feeding</b>	Automatic or manual sheet feeding	
<b>Document Size</b>		
Width	53 - 300mm (2 - 11.8in.)	
Length	70 - 432mm (2.75 - 17.01in.)	
	Long Document Mode:	up to 3,000mm (118.1in.)
<b>Document Thickness and Weight</b>		
U-Turn path	Automatic feeding:	0.06 - 0.15mm, 52 - 128g/m <sup>2</sup> (14 - 32lb. bond)
	Manual Feeding:	0.05 - 0.2mm, 42 - 157g/m <sup>2</sup> (11 - 40lb. bond)
Straight path	Automatic feeding:	0.06 - 0.15mm, 52 - 128g/m <sup>2</sup> (14 - 32lb. bond)
	Manual Feeding:	0.05 - 0.66mm, 42 - 546g/m <sup>2</sup> (11 - 144lb. bond)

<b>Business Card Size and Thickness</b>		
Size	53.9 x 85.5mm (2.12 x 3.37in.)	
Thickness	0.76 ± 0.08mm (0.03 ± 0.003in.)	
<b>Feeding Capacity</b>	10mm stack or 100 sheets of 80g/m <sup>2</sup> (20lb. bond)	
<b>Scanning Element</b>	3-line CMOS CIS	
<b>Light Source</b>	LED (red, green, and blue)	
<b>Scanning Side</b>	Simplex / Duplex	
<b>Scanning Modes</b>	Black and White, Error Diffusion, High-Speed Text Enhancement, Advanced Text Enhancement, Advanced Text Enhancement II, 256-level Grayscale, 24-bit Colour, Auto Color Detection	
<b>Scanning Resolutions</b>	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi	
<b>Scanning Speed (A4 / LTR, Portrait)</b>		
Black and White	200dpi:	60ppm (Simplex), 120ipm (Duplex)
	300dpi:	60ppm (Simplex), 120ipm (Duplex)
256-level Grayscale	200dpi:	60ppm (Simplex), 120ipm (Duplex)
	300dpi:	60ppm (Simplex), 120ipm (Duplex)
24-bit Colour	200dpi:	60ppm (Simplex), 120ipm (Duplex)
	300dpi:	60ppm (Simplex), 84ipm (Duplex)
<b>Interfaces</b>	SCSI-III / Hi-Speed USB 2.0	
<b>Scanner Driver</b>	ISIS / TWAIN	
<b>Useful Functions</b>	Ultrasonic Double Feed Detection, Continuous Mode, Moire Reduction, Prevent Bleed Through / Remove Background, Punch Hole Removal, Color Dropout, Auto Page Size Detection, Text Orientation Recognition, Skip Blank Page, Deskew, MultiStream™, Prescan, User Preferences, Skew Detection, Gamma Correction, Remove Border, Isolated Point Removal, Edge emphasis, Add-on	
<b>Power Requirements</b>	AC220 - 240V (50 / 60Hz)	

<b>Power Consumption</b>	46.5W (Scanning), 3.7W (Sleep Mode)	
<b>Operating Environment</b>	10 - 32.5°C (50 - 90.5°F)	
	Humidity:	20 - 80% RH
<b>Dimensions (W x D x H)</b>	Feed trays closed:	398.4 x 312 x 191.4mm (15.6 x 12.3 x 7.5in.)
<b>Weight</b>	Approx. 10.5kg (23lb.)	
<b>Options / Consumables</b>	Barcode Module, Exchange Roller Kit	

**Specifications are subject to change without notice. :**

- When scanning documents using ADF.
- Actual scanning speed may vary depending on your system configuration and PC.



- **Address :** Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No:** +022-28460505 (50 lines)
- **Email:** [itsolutions@varay.co.in](mailto:itsolutions@varay.co.in)