

## Specifications for DR X10C



|                                      |   |   |
|--------------------------------------|---|---|
| <b>Type</b>                          | Desktop sheetfed scanner  |   |
| <b>Document Feeding</b>              | Automatic or manual sheet feeding   |   |
| <b>Document size</b>                 | Width:  | 50.8 - 305mm (2 - 12.01in.)                               |
|                                      | Length:   | 70 - 432mm (2.76 - 17.01in.)                              |
| <b>Document thickness and weight</b> | Automatic feeding:  | 0.06 - 0.15mm, 52 - 128g/m <sup>2</sup> (14 - 32lb. bond) |
|                                      | Manual feeding:   | 0.05 - 0.30mm, 42 - 255g/m <sup>2</sup> (11 - 64lb. bond) |
| <b>Feeding capacity</b>              | Up to 500 sheets of good quality paper (48mm or less including page curl)   |   |
| <b>Scanning element</b>              | 3-line CMOS CIS   |   |
| <b>Light Source</b>                  | LED (red, green, and blue)  |   |
| <b>Scanning Side</b>                 | Simplex / Duplex  |   |
| <b>Scanning Modes</b>                | Black and White, Error Diffusion, Advanced Text Enhancement, Advanced Text Enhancement II<br>256-level Grayscale<br>24-bit Colour |   |
| <b>Scanning Resolutions</b>          | 100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi,<br>400 x 400dpi, 600 x 600dpi                               |   |

|   |   |                                    |
|---|---|------------------------------------|
| <b>Scanning speed*<sup>1</sup> (A4 / LTR, Portrait, 200dpi)</b> |   |                                    |
| Portrait  | Black and White:  | 100ppm (Simplex) / 200ipm (Duplex) |
|   | Grayscale:  | 100ppm (Simplex) / 200ipm (Duplex) |
|   | Colour:   | 100ppm (Simplex) / 200ipm (Duplex) |
| Landscape   | Black and White:  | 130ppm (Simplex) / 260ipm (Duplex) |
|   | Grayscale:  | 130ppm (Simplex) / 260ipm (Duplex) |
|   | Colour:   | 130ppm (Simplex) / 260ipm (Duplex) |
| <b>Useful functions</b>   | Job Function, Ultrasonic Double Feed Detection, Staple Detection, Selectable Background Colour, Dust Countermeasures, Auto USB Power Switching, Auto Colour Detection, Moiré Reduction, Prevent Bleed Through / Remove Background, User Registration, Skip Blank Page, Auto Page Size Detection, Deskew, Batch Separation, Text Orientation Recognition, Black Border Removal, Punch Hole Removal, Folio, Long Document Mode, Colour Dropout / Enhancement (R/G/B/Custom), MultiStream™ |                                    |
| <b>Interfaces</b>   | Dual Interface (SCSI-3 & High-Speed USB2.0)   |                                    |
| <b>Software</b>   | ISIS / TWAIN Driver, Job Registration Tool, CapturePerfect 3.0  |                                    |
| <b>Power requirements</b>                                       | AC 100V (50 / 60Hz), AC 120V (60Hz), AC 220 - 240V (50 / 60Hz)  |                                    |
| <b>Power Consumption</b>  | Scanning:   | 125W                               |
|   | Sleep mode:   | 4.2W (AC 220 - 240V: 4.5W)         |
|   | Power Turned Off:   | 0W                                 |
| <b>Operating environment</b>                                    | 10 - 32.5°C (50 - 90.5°F)   |                                    |
|   | Humidity:   | 20 - 80% RH                        |
| <b>Dimensions (W x D x H)</b>                                   | 528 x 563 x 375mm (20.79 x 22.17 x 14.77in.), with trays closed   |                                    |
| <b>Weight</b>   | Approx. 39kg (86lb.)  |                                    |
| <b>Optionals</b>  | Pre-Imprinter Unit, Post-Imprinter Unit, Patch Code Decoder, Barcode Module III   |                                    |
| <b>Consumables</b>  | Exchange Roller Kit (Feed roller, Retard roller, Pick roller), Cleaning Sheets (30), Ink Cartridges for Imprinter   |                                    |

Specifications are subject to change without notice.

- Actual scanning speed may vary depending on your system configuration and PC.

\*<sup>1</sup> When scanning documents using ADF.  
Maximum hardware speed.



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: +022-28460505 (50 lines)
- **Email**: [itsolutions@varay.co.in](mailto:itsolutions@varay.co.in)